



40 YEARS OF
FinOlex
PIPES



SOLVENT CEMENT, PRIMER & LUBRICANT

PRODUCT CATALOGUE

📞 1800 200 3466 | 🌐 finolexpipes.com

SOLVENT CEMENT

Finolex solvent cement is manufactured under license from Invogue Labs Inc. New York, USA. With our strict in-house quality control, we offer superior quality every time. Our solvent cement facilitates strong and consistent joint between pipe to pipe, fitting to fitting, or pipe to fitting combinations.

Finolex solvent cement can be dependably used in agriculture, sanitation, PVC-U and CPVC plumbing.

With our advanced R&D initiatives, we have developed low VOC (Volatile Organic Compounds) products to ensure high-quality performance and installation, while being environmentally friendly and beneficial to the applicator.



PVC-U SOLVENT CEMENT FOR AGRICULTURE APPLICATIONS UPTO 110MM (4")
ASTM D-2564, AS PER IS 14182

ml	100	250	500	1000	5000
Container	Tin	Tin	Tin	Tin	Can



CPVC SOLVENT CEMENT FOR HOT AND COLD WATER PLUMBING APPLICATIONS YELLOW MEDIUM BODIED (UPTO 2")
ASTM F-493

ml	59	118	237	473	946
Container	Tin	Tin	Tin	Tin	Tin



PVC-U SOLVENT CEMENT FOR HIGHER DIAMETER AGRICULTURE APPLICATIONS ABOVE 110 MM (4")
ASTM D-2564, AS PER IS 14182

ml	250	500	1000	5000
Container	Tin	Tin	Tin	Can



CPVC SOLVENT CEMENT FOR HOT AND COLD WATER PLUMBING APPLICATIONS ORANGE HEAVY BODIED (ABOVE 2")
ASTM F-493

ml	118	237	473	946
Container	Tin	Tin	Tin	Tin



MEDIUM DUTY PVC-U SOLVENT CEMENT FOR PLUMBING APPLICATIONS UPTO 50MM (2")
ASTM D-2564

ml	118	237	473
Container	Tin	Tin	Tin



PVC-U SOLVENT CEMENT FOR SWR (SELFIT) APPLICATIONS
As per IS 14182

ml	100	250	500	1000
Container	Tin	Tin	Tin	Tin



HEAVY DUTY PVC-U SOLVENT CEMENT FOR PLUMBING APPLICATIONS ABOVE 50MM (2")
ASTM D-2564

ml	118	237	473
Container	Tin	Tin	Tin



PRIMER FOR PVC-U AND CPVC PLUMBING APPLICATIONS
ASTM F-656

ml	237
Container	Tin



RUBBER LUBRICANT

gms	50	100	250	500	1000
Container	Plastic Container				

PRECAUTIONS




- Avoid prolonged breathing of solvent vapors. It is recommended to wear a mask when working in enclosed areas.
- Keep solvent cement away from all sources of ignition, heat, sparks, and open flame.
- Close solvent cement containers tightly after use.
- Avoid eye and skin contact.
- Store solvent cements in a cool area.
- Brush must be clean and dry before commencing solvent welding process.
- System should be pressure tested before concealment.
- Do not attempt to cement in rain or in the presence of moisture.
- Solvent cement should be used within the expiry period mentioned on the container.







**SOLVENT
CEMENT, PRIMER
& LUBRICANT**

FEATURES & BENEFITS:




SOLVENT CEMENTS:

-  Low VOC emissions make it environmentally friendly
-  High-quality applicator for user-friendly and smooth application
-  Colour coded solvent packaging for ease of identification and inspection

LUBRICANT:

-  Finolex lubricant is a non-toxic, soft paste like material that is non-flammable
-  Lubricant is used for easy installation of all types of Ringfit pipes. It helps smooth insertion of pipes and fittings
-  Keeps the rubber and plastic gasket safe
-  Easy to clean

PRIMER:

-  Use of primer will increase joint strength
-  Use of primer (ASTM F 656) prior to solvent cement joint is essential for 65 mm (2.1/2") and above size of pipes.
-  The container (tin) has a unique design with an integrated brush in the cap. This ensures airtight closure and reduces contamination

Finolex Industries Limited


Registered Office:

Gat No. 399, Village Urse, Taluka Maval, District Pune - 410 506. Maharashtra, India.
Tel. No. : 02114 - 237251 | E-mail: investors@finolexind.com
CIN: L40108PN198PLC024153 | Website: www.finolexpipes.com

Corporate Office:

D1/10, MIDC, Chinchwad, Pune - 411 019. Maharashtra, India.
Tel. No. : 020 - 27408200
E-mail: care@finolexpipes.com

Follow us on:     



Disclaimer:

• Specifications are subject to change without prior notice. • The product images shown are for illustration purposes only and may not be an exact representation of the product. • The product images or other information cannot be construed as guarantee or suitability for a particular application. • Warranty applicable only for manufacturing defects when products are installed as per our standard guidelines and usage. • Warranty is not applicable if any other brand's products are used in combination with Finolex products. • In any case, the manufacturer/ seller's liability towards any claim is limited to replacement of, or credit for the defective product excluding any allied or incidental expenses. The manufacturing defect should be brought to notice within 24 months from manufacturing date.